

SAFETY-KLEEN 105 SOLVENT RECYCLED MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT NAME: SAFETY-KLEEN 105 SOLVENT RECYCLED

SYNONYMS: Parts Washer Solvent; Petroleum Distillates; Petroleum Naptha;
Naptha, Solvent; Stoddard Solvent; Mineral Spirits.

PRODUCT PART

NUMBERS: 6614, 6617, 1011662, 1014662.

PRODUCT USE: Cleaning and degreasing metal parts.

If this product is used in combination with other products, refer to the Material Safety Data Sheets for those products.

24-HOUR EMERGENCY PHONE NUMBERS

These numbers are for **MEDICAL: TRANSPORTATION (SPILL): emergency use only. If you desire non-emergency 1-800-752-7869 1-800-468-1760**

product information,

please call a phone

number listed below.

SUPPLIER: Safety-Kleen Systems, Inc.

5400 Legacy Drive
Cluster II, Building 3
Plano, Texas 75024
USA

1-800-669-5740

TECHNICAL INFORMATION: 1-800-669-5740, Press 1 then Extension 7500

MSDS FORM NUMBER: 82310	ISSUE: November 27, 2002
ORIGINAL ISSUE: April 8, 1976	SUPERSEDES: March 24, 2000
PREPARED BY: Product MSDS Coordinator	APPROVED BY: MSDS Task Force

Revision 11/02; MSDS Form No. 82310 - Page 1 of 11 **SAFETY-KLEEN 105**

SOLVENT RECYCLED MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

Revision 11/02; MSDS Form No. 82310 - Page 2 of 11

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

OSHA PEL				ACGIH TLV®					
WT%	NAME	SYNONYM	CAS NO.	TWA	STEL	TWA	STEL	LD	LC
99 to 100	Distillates (petroleum), hydrotreated lighte	N.Av.	64742-47-8 500d	ppm	N.Av.	100d ppm	N.Av.	>5000g, c	>5500d, h mg/m3/4 hours
0 to 0.2*	Tetrachloroethene	Perchloroethylene; Tetrachloroethylene	127-18-4	100 ppm	200 ppm (ceiling)	25 ppm	100 ppm	2629a,f	34200b mg/m3/8 hours

<p>N.Av. = Not Available *Even though the concentration range does not fall under the ranges prescribed by WHMIS, this is the actual range which varies with each batch of the product. aOral-Rat LD50 (mg/kg)</p>	<p>bInhalation-Rat LC50 cBased on Stoddard solvent: Skin-Rabbit LD50 >3000 mg/kg dBased on Stoddard Solvent.</p>	<p>eBased on Stoddard Solvent, NIOSH IDLH (Immediately Dangerous to Life or Health): 20000 mg/m³ (5000 ppm) fSkin-Rabbit LD50 >10000 mg/kg gOral-Rat LD (mg/kg) hInhalation-Rat LC</p>
--	---	---

SECTION 3: HAZARDS IDENTIFICATION EMERGENCY OVERVIEW

APPEARANCE

Liquid, clear and green, mild hydrocarbon odor.

WARNING!

PHYSICAL HAZARD

Combustible liquid and vapor.

HEALTH HAZARDS

May be harmful if inhaled.

May irritate eyes and skin.

May be harmful if swallowed.

Suspect cancer hazard. Contains material (less than 0.3 WT%) which may cause cancer. Risk of cancer depends on duration and level of exposure.

Contains material which may cause birth defects.

Contains material which may cause central nervous system damage.

ENVIRONMENTAL HAZARDS

Toxic to aquatic life.

SAFETY-KLEEN 105 SOLVENT RECYCLED MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

POTENTIAL HEALTH EFFECTS

INHALATION High concentrations of vapor or mist may be harmful if inhaled.

High

(BREATHING): concentrations of vapor or mist may irritate the respiratory tract (nose, throat, and lungs). High concentrations of vapor or mist may cause nausea, vomiting, headaches, dizziness, loss of coordination, numbness, and other central nervous system effects. Massive acute overexposure may cause rapid central nervous system depression, sudden collapse, coma, and/or death.

EYES: May cause irritation with watering, stinging, and/or redness.

SKIN: May cause irritation. Not likely to be absorbed through the skin in harmful amounts.

INGESTION May be harmful if swallowed. May cause throat irritation, nausea, vomiting,

(SWALLOWING): and central nervous system effects as noted under

INHALATION

(BREATHING). Breathing product into the lungs during ingestion or vomiting may cause lung injury and possible death.

MEDICAL CONDITIONS Individuals with pre-existing respiratory tract (nose,

throat, and
AGGRAVATED BY lungs), central nervous system, eye, and/or skin disorders
may have

EXPOSURE: increased susceptibility to the effects of exposure.

CHRONIC: Prolonged or repeated inhalation may cause toxic effects as noted under **INHALATION (BREATHING)**. Prolonged or repeated inhalation and/or ingestion has been suggested to produce kidney toxicity in dogs but in no other species, including humans. According to one unsubstantiated human case report, prolonged or repeated inhalation, skin contact, and/or ingestion may cause mild, acute chemical hepatitis and acute, yellow atrophy (size reduction) of the liver. Prolonged or repeated eye contact may cause inflammation of the membrane lining the eyelids and covering the eyeball (conjunctivitis). Prolonged or repeated skin contact may cause drying, cracking, redness, itching, and/or swelling (dermatitis); and/or burns.

CANCER This product contains perchloroethylene which may cause cancer.
Risk of

INFORMATION: cancer depends on duration and level of exposure. For more information,

see **SECTION 11: CARCINOGENICITY**.

Also see **SECTION 15: CALIFORNIA**.

POTENTIAL ENVIRONMENTAL EFFECTS

Product is toxic to aquatic life. Also see **SECTION 12: ECOLOGICAL INFORMATION**.

Revision 11/02; MSDS Form No. 82310 - Page 3 of 11 **SAFETY-KLEEN 105**

SOLVENT RECYCLED MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

Revision 11/02; MSDS Form No. 82310 - Page 4 of 11

SECTION 4: FIRST AID MEASURES

INHALATION: Remove to fresh air. If not breathing, give artificial respiration. If breathing

(BREATHING) is difficult, give oxygen. Oxygen should only be administered by qualified personnel. Someone should stay with victim. Get medical attention if breathing difficulty persists.

EYES: If irritation or redness from exposure to vapor develops, move away from exposure into fresh air. Upon contact, immediately flush eyes with plenty of lukewarm water, holding eyelids apart, for 15 minutes. Get medical attention.

SKIN: Remove affected clothing and shoes. Wash skin thoroughly with soap and water. Get medical attention if irritation or pain develops or persists.

INGESTION: Do NOT induce vomiting. Immediately get medical attention. Call **(SWALLOWING)** 1-800-752-7869 for additional information.

If spontaneous vomiting occurs, keep head below hips to avoid breathing the product into the lungs. Never give anything to an unconscious person by mouth.

NOTE TO Treat symptomatically and supportively. Administration of gastric lavage,

PHYSICIANS: if warranted, should be performed by qualified medical personnel. Treatment may vary with condition of victim and specifics of incident. Call 1-800-752-7869 for additional information.

SECTION 5: FIRE FIGHTING MEASURES

FLASH POINT: 105°F (40°C) (minimum) Tag Closed Cup

FLAMMABLE LIMITS IN AIR: LOWER: 0.7 VOL% (minimum)

UPPER: 5 VOL% (maximum)

AUTOIGNITION

TEMPERATURE: 410°F (210°C) (minimum)

HAZARDOUS COMBUSTION Decomposition and combustion materials may be toxic.

PRODUCTS: Burning may produce carbon monoxide and unidentified organic compounds.

CONDITIONS OF

FLAMMABILITY: Heat, sparks, or flame.

EXTINGUISHING MEDIA: Carbon dioxide, regular foam, dry chemical, water spray, or water fog.

SAFETY-KLEEN 105 SOLVENT RECYCLED MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

NFPA 704

HAZARD This information is intended solely for the use by individuals

IDENTIFICATION: trained in this system.

FIRE FIGHTING Keep storage containers cool with water spray.

INSTRUCTIONS: A positive-pressure, self-contained breathing apparatus (SCBA) and full-body protective equipment are required for fire emergencies.

FIRE AND Vapor explosion hazard indoors, outdoors, or in sewers.

EXPLOSION HAZARDS: Vapors may travel to ignition source and flashback. Vapors will spread along the ground and collect in low or confined areas. Run-off to sewer may create a fire hazard. Heated containers may rupture. "Empty" containers may retain residue and can be dangerous. Not sensitive to mechanical impact. Product may be sensitive to static discharge, which could result in fire or explosion.

SECTION 6: ACCIDENTAL RELEASE MEASURES

Remove all ignition sources. Do not touch or walk through spilled product. Stop leak if you can do it without risk. Wear protective equipment and provide engineering controls as specified in **SECTION 8: EXPOSURE**

CONTROLS/PERSONAL PROTECTION. Isolate hazard area. Keep unnecessary and unprotected personnel from entering. Ventilate area and avoid breathing vapor or mist. A vapor suppressing foam may be used to reduce vapors. Contain spill away from surface waters and sewers. Contain spill as a

liquid for possible recovery or sorb with compatible sorbent material and shovel with a clean, sparkproof tool into a sealable container for disposal.

Additionally, for large spills: Water spray may reduce vapor, but may not prevent ignition in closed spaces. Dike far ahead of liquid spill for collection and later disposal.

There may be specific federal regulatory reporting requirements associated with spills, leaks, or releases of this product. Also see **SECTION 15: REGULATORY INFORMATION**.

Revision 11/02; MSDS Form No. 82310 - Page 5 of 11 **SAFETY-KLEEN 105**

SOLVENT RECYCLED MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

Revision 11/02; MSDS Form No. 82310 - Page 6 of 11

SECTION 7: HANDLING AND STORAGE

HANDLING: Keep away from heat, sparks, or flame. Where flammable mixtures may be present, equipment safe for such locations should be used. Use clean, sparkproof tools and explosion-proof equipment. When transferring product, metal containers, including trucks and tank cars, should be grounded and bonded. Do not breathe vapor or mist. Use in a well ventilated area. Avoid contact with eyes, skin, clothing, and shoes. Do not smoke while using this product.

SHIPPING AND Keep container tightly closed when not in use and during transport. Do not

STORING: pressurize, cut, weld, braze, solder, drill, or grind containers. Keep containers away from heat, flame, sparks, static electricity, or other sources of ignition. Empty product containers may retain product residue and can be dangerous. See **SECTION 14: TRANSPORT INFORMATION** for Packing Group information.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING Provide general ventilation needed to maintain concentration of vapor or

CONTROLS: mist below applicable exposure limits. Where adequate general ventilation is unavailable, use process enclosures, local exhaust ventilation, or other engineering controls to control airborne levels below recommended exposure limits. Where explosive mixtures may be present, equipment safe for such locations should be used.

PERSONAL PROTECTIVE EQUIPMENT

RESPIRATORY Use NIOSH-certified, air-purifying respirators with organic vapor cartridges

PROTECTION: respiratory protective equipment when concentration of vapor or mist exceeds applicable exposure limits. Protection provided by air-purifying respirators is limited. Selection and use of respiratory protective equipment should be in accordance in the USA with OSHA General Industry Standard 29 CFR 1910.134; or in Canada with CSA Standard Z94.4.

EYE Where eye contact is likely, wear chemical goggles; contact lens use
PROTECTION: is not recommended.

SKIN Where skin contact is likely, wear nitrile, supported neoprene, Viton®,
PROTECTION: polyvinyl alcohol (PVA), laminate (such as North Silver Shield®,
Safety 4 4h®, Ansell Edmont Barrier®), or equivalent
protective gloves; use of polyvinyl chloride (PVC), natural
rubber (latex), or equivalent gloves is not recommended.

SAFETY-KLEEN 105 SOLVENT RECYCLED MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

To avoid prolonged or repeated contact where spills and splashes are likely,
wear appropriate chemical-resistant faceshield, boots,
apron, whole body suits, or other protective clothing.

PERSONAL HYGIENE: Use good personal hygiene. Wash thoroughly with soap and water
after handling product and before eating, drinking, or using tobacco
products. Clean affected clothing, shoes, and protective
equipment before reuse. Discard affected clothing, shoes, or
protective equipment if they cannot be thoroughly cleaned.
Discard leather articles, such as shoes, saturated with the
product.

OTHER Where spills and splashes are likely, facilities storing or using this
product

PROTECTIVE should be equipped with an emergency eyewash and shower,
both

EQUIPMENT: equipped with clean water, in the immediate work area.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

PHYSICAL STATE,

APPEARANCE, AND ODOR: Liquid, clear and green, mild hydrocarbon odor.

ODOR THRESHOLD: 30 ppm (based on Stoddard Solvent)

MOLECULAR WEIGHT: Not available.

SPECIFIC GRAVITY: 0.77 to 0.80 at 60°F/60°F (15.6°C/15.6°C) (water = 1)

DENSITY: 6.4 to 6.7 LB/US gal (770 to 800 g/l)

VAPOR DENSITY: 5 (air = 1) (approximately)

VAPOR PRESSURE: 0.4 mm Hg at 68°F (20°C) (approximately)

1.0 mm Hg at 100°F (38°C) (approximately)

BOILING POINT: 310°F (155°C) (initial)

FREEZING/MELTING POINT: -45°F (-43°C) (maximum)

pH: Not applicable.

EVAPORATION RATE: 0.1 (butyl acetate = 1) (based on Stoddard Solvent)

SOLUBILITY IN WATER: Insoluble.

FLASH POINT: 105°F (40°C) (minimum) Tag Closed Cup

Revision 11/02; MSDS Form No. 82310 - Page 7 of 11 **SAFETY-KLEEN 105**

SOLVENT RECYCLED MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

FLAMMABLE LIMITS IN AIR: LOWER: 0.7 VOL% (minimum)

UPPER: 5 VOL% (maximum)

AUTOIGNITION

TEMPERATURE: 410°F (210°C) (minimum)

SECTION 10: STABILITY AND REACTIVITY

STABILITY: Stable under normal temperatures and pressures. Avoid heat, sparks, or flame.

INCOMPATIBILITY: Avoid acids, alkalis, oxidizing agents, reducing agents, reactive halogens, or reactive metals.

REACTIVITY: Polymerization is not known to occur under normal temperatures and pressures. Not reactive with water.

HAZARDOUS

DECOMPOSITION None under normal temperatures and pressures. See

PRODUCTS: also **SECTION 5: HAZARDOUS COMBUSTION PRODUCTS.**

SECTION 11: TOXICOLOGICAL INFORMATION

SENSITIZATION: Based on best current information, there is no known human sensitization associated with this product.

MUTAGENICITY: Perchloroethylene has demonstrated animal effects of mutagenicity.

Based on best current information, the other component listed in **SECTION 2** is not a mutagen.

CARCINOGENICITY: Perchloroethylene is categorized by IARC as probably carcinogenic to humans (Group 2A). Perchloroethylene is listed by NTP as having limited evidence of carcinogenicity in humans or sufficient evidence of carcinogenicity in experimental animals. Perchloroethylene is categorized by ACGIH as a confirmed animal carcinogen with unknown relevance to humans (A3). This agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histologic type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiologic studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure.

Revision 11/02; MSDS Form No. 82310 - Page 8 of 11 **SAFETY-KLEEN 105**
SOLVENT RECYCLED MATERIAL SAFETY DATA SHEET FOR
USA AND CANADA

Based on best current information, the other component listed in **SECTION 2** is not a carcinogen.

Also see **SECTION 3: CANCER INFORMATION** and **SECTION 15: CALIFORNIA.**

REPRODUCTIVE Based on best current information, there is no known reproductive

TOXICITY: toxicity associated with this product.

Also see **SECTION 15: CALIFORNIA.**

TERATOGENICITY: Perchloroethylene has demonstrated animal effects of

teratogenicity.

Based on best current information, the other component listed in

SECTION 2 is not a teratogen.

TOXICOLOGICALLY Based on best current information, there are no known **SYNERGISTIC** toxicologically synergistic products associated with this **PRODUCT(S)**: product.

SECTION 12: ECOLOGICAL INFORMATION

ECOTOXICITY: 2900 ug/L 96 hour LC50 Rainbow trout, donaldson trout
(*Oncorhynchus mykiss*) (based on Distillates
(petroleum) hydrotreated light).

OCTANOL/WATER

PARTITION COEFFICIENT: Not available.

VOLATILE ORGANIC 100 WT%; 6.4 to 6.7 LB/US gal; 770 to 800 g/l

COMPOUNDS: As per 40 CFR Part 51.100(s).

SECTION 13: DISPOSAL CONSIDERATIONS

DISPOSAL: Dispose in accordance with federal, state, provincial, and local regulations. Regulations may also apply to empty containers. The responsibility for proper waste disposal lies with the owner of the waste. Contact Safety-Kleen regarding recycling or proper disposal.

USEPA WASTE D001, D018, D039, and D040

CODE(S): Based on available data, this information applies to the product as supplied to the user. Processing, use, or contamination by the user may change the waste code(s) applicable to the disposal of this product.

Revision 11/02; MSDS Form No. 82310 - Page 9 of 11 **SAFETY-KLEEN 105**

SOLVENT RECYCLED MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

Revision 11/02; MSDS Form No. 82310 - Page 10 of 11

SECTION 14: TRANSPORT INFORMATION

DOT: COMBUSTIBLE LIQUID, N.O.S. (PETROLEUM NAPHTHA),
NA1993, PG III

TDG: Petroleum Distillates, N.O.S., Class 3, UN1268, PG III

EMERGENCY RESPONSE 128

GUIDE NUMBER: Reference *North American Emergency Response Guidebook*

SECTION 15: REGULATORY INFORMATION

USA REGULATIONS

SARA SECTIONS Based on the ingredients listed in **SECTION 2**, this product does not

302 AND 304: contain any "extremely hazardous substances" listed pursuant to Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) Section 302 or Section 304 as identified in 40 CFR Part 355, Appendix A and B.

SARA SECTIONS This product poses the following physical and health hazards as

311 AND 312: defined in 40 CFR Part 370 and is subject to the requirements of sections 311 and 312 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA):
 Immediate (Acute) Health Hazard
 Delayed (Chronic) Health Hazard
 Fire Hazard

SARA SECTION 313: The following component is subject to the requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372.

Material	CAS
Perchloroethylene	127-18-4

CERCLA: Based on the ingredients listed in **SECTION 2**, this product contains the following "hazardous substance" listed under the Comprehensive Environmental Response, Compensation and Liability Act of 1980 (CERCLA) in 40 CFR Part 302, Table 302.4 with the following reportable quantity (RQ):

Material	CAS RQ	
Perchloroethylene	127-18-4	100 LB (15.4 kg)

TSCA: All the components of this product are listed on the TSCA Inventory.

SAFETY-KLEEN 105 SOLVENT RECYCLED MATERIAL SAFETY DATA SHEET FOR USA AND CANADA

CALIFORNIA: This product may contain detectable amounts of benzene CAS 71-43-2, p-dichlorobenzene CAS 106-46-7, methylene chloride CAS 75-09-2, perchloroethylene CAS 127-18-4, and trichloroethylene CAS 79-01-6. **WARNING:** These chemicals are known to the State of California to cause cancer.

This product may contain detectable amounts of benzene CAS 71-43-2 and toluene CAS 108-88-3. **WARNING:** These chemicals are known to the State of California to cause birth defects or other reproductive harm.

CANADIAN REGULATIONS

This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations (CPR) and the MSDS contains all the information required by the CPR.

WHMIS: B3, D2A, D2B

CANADIAN

ENVIRONMENTAL

PROTECTION ACT (CEPA): All the components of this product are listed on the Canadian Domestic Substances List (DSL).

SECTION 16: OTHER INFORMATION

REVISION INFORMATION: Updated with Safety-Kleen Texas address, modified

Medical Emergency phone number,
modification to Transportation Spill number,
and modification of Technical Information
phone number.

LABEL/OTHER INFORMATION: This product is United States Department of
Agriculture (USDA) approved, Underwriter's
Laboratories (UL) classified, and Factory
Mutual (FM) approved.

User assumes all risks incident to the use of this product. To the best of our knowledge, the information contained herein is accurate. However, Safety-Kleen assumes no liability whatsoever for the accuracy or completeness of the information contained herein. No representations or warranties, either express or implied, or merchantability, fitness for a particular purpose or of any other nature are made hereunder with respect to information or the product to which information refers. The data contained on this sheet apply to the product as supplied to the user.

ÆÉ2000 Printed in the USA.

Revision 11/02; MSDS Form No. 82310 - Page 11 of 11